

BULLARD ABRASIVES®



INDUSTRIAL PERFORMANCE

Specifically manufactured for maximum performance on a multitude of work place materials, for ductile iron, masonry, steel, rail and decking applications.

Our range of wheels are requested from job site to job site.

Engineered to perform under the toughest operating environments where consistency and dependability are required.

TYPE 1

Since 1927
Made In The USA
ISO 9001: 2015 Certified



gas or electric portable saw CUT-OFF WHEELS

TYPE 1

TA24R HIGH ENERGY

	PART#	MAX RPM	DIMENSIONS	QTY
THIN METALS, ROOF, DECKING, CAR DISMANTLING	84235	6,360	12 x 1/8 x 1	10
	84236	6,360	12 x 1/8 x 20mm	10
	84435	5,460	14 x 1/8 x 1	10
	84436	5,460	14 x 1/8 x 20mm	10

PA24R HIGH ENERGY

	PART#	MAX RPM	DIMENSIONS	QTY
FERROUS METALS (STRUCTURAL STEEL, IRON, REBAR, ETC)	82234	6,360	12 x 1/8 x 1	10
	82133	6,360	12 x 1/8 x 20mm	10
TREATED AO GRAIN 1/64" THICKER	82433	5,460	14 x 1/8 x 1	10
	82434	5,460	14 x 1/8 x 20mm	10

AC24R HIGH ENERGY

	PART#	MAX RPM	DIMENSIONS	QTY
DUCTILE PIPE, CAST IRON,	88233	6,360	12 x 1/8 x 1	10
CONCRETE, COATED STEEL, SEWER AND WATER MAINS	88133	6,360	12 x 1/8 x 20mm	10
	88433	5,460	14 x 1/8 x 1	10
	88434	5,460	14 x 1/8 x 20mm	10
	88633	4,800	16 x 1/8 x 1	5
	88634	4,800	16 x 1/8 x 20mm	5

PC24R HIGH ENERGY

	PART#	MAX RPM	DIMENSIONS	QTY
CURED CONCRETE, MASONRY, BRICK, BLOCK AND STONE 1/64" THICKER	82231	6,360	12 x 1/8 x 1	10
	82130	6,360	12 x 1/8 x 20mm	10
	82430	5,460	14 x 1/8 x 1	10
	82431	5,460	14 x 1/8 x 20mm	10

A24R LIGHTNING

	PART#	MAX RPM	DIMENSIONS	QTY
FERROUS METALS (STRUCTURAL STEEL, IRON, REBAR, ETC)	84234	6,360	12 x 1/8 x 1	10
	84133	6,360	12 x 1/8 x 20mm	10
	84433	5,460	14 x 1/8 x 1	10
	84434	5,460	14 x 1/8 x 20mm	10
	84633	4,800	16 x 1/8 x 1	5
	84634	4,800	16 x 1/8 x 20mm	5

C24R LIGHTNING

	PART#	MAX RPM	DIMENSIONS	QTY
CURED CONCRETE, MASONRY, BRICK, BLOCK AND STONE	80231	6,360	12 x 1/8 x 1	10
	80130	6,360	12 x 1/8 x 20mm	10
	80430	5,460	14 x 1/8 x 1	10
	80431	5,460	14 x 1/8 x 20mm	10
	80630	4,800	16 x 1/8 x 1	5
	80631	4,800	16 x 1/8 x 20mm	5

CC20R LIGHTNING

	PART#	MAX RPM	DIMENSIONS	QTY
ASPHALT AND GREEN CONCRETE, CURED CONCRETE AND MASONRY	81231	6,360	12 x 1/8 x 1	10
	81130	6,360	12 x 1/8 x 20mm	10
	81430	5,460	14 x 1/8 x 1	10
	81431	5,460	14 x 1/8 x 20mm	10

HIGH ENERGY portable cut-off saw specifications are designed to be versatile performers on all types and sizes of metal and masonry materials. Utilizing a special bond system developed by Bullard engineers, these wheels out cut and out last competitors while offering excellent value on a price/performance ratio.

LIGHTNING specifications offer industrial performance at a modest price. Manufactured in the USA, the quality and high-performance in both metal and concrete formulations exceed the performance of lower cost imports yet only cost a fraction more. A real value for the budget minded buyer.

BULLARD ABRASIVES®
surfaces be warned...

